




R18 SPECIFICATIONS Teeth




GPE




VE




WE




FE



AE



GPL




AL

Typical machine weight - Excavator 17-25 MT
Maximum breakout force in HD/XHD 147 kN


Typical machine weight - Loader 17-25 MT
Maximum breakout force in HD/XHD 265 kN

Type	Part. no			A mm	B mm	C mm	D mm	E mm	Weight kg
GPE	R18GPE			267	111	12	92	108	6.6
VE	R18VE			294	111	11	11	108	5.8
WE	R18WE			294	111	11	137	108	7.0
FE	R18FE			273	111	14	182	108	9.1
AE	R18AE			290	111	20	109	108	8.5
GPL	R18GPL			267	111	11	92	108	7.5
AL	R18AL			298	111	17	94	108	10.0


R I 8 SPECIFICATIONS Adapters, Accessories




BE




SL



TL



LP



LR



LT

Type	Part. no			A mm	B mm	C mm	D mm	E mm	F mm	G bevel°	Weight kg
BE	R I 8BE40			42	361	106	120	220	119	30°	11.9
BE	R I 8BE45			47	362	106	119	221	119	30°	12.1
SL	R I 8SL30			30 (30-40)	357	106	N/A	N/A	114	25°	12.8
TL	R I 8TL40			42	356	106	215	125	121	25°	12.8
LP	R I 8LP			25	90						0.2
LR	R I 8LR			35							-
LT	R I 8LT			408	65						0.6