




R23 SPECIFICATIONS Teeth




GPE




VE




WE




FE



AE



GPL




AL

Typical machine weight - Excavator 25-35 MT
 Maximum breakout force in HD/XHD 184 kN


Typical machine weight - Loader 25-35 MT
 Maximum breakout force in HD/XHD 331 kN

Type	Part. no			A mm	B mm	C mm	D mm	E mm	Weight kg
GPE	R23GPE			301	125	14	104	122	9.6
VE	R23VE			332	125	12	13	122	8.4
WE	R23WE			332	125	12	155	122	10.1
FE	R23FE			309	125	16	205	122	13.1
AE	R23AE			328	125	22	123	122	12.4
GPL	R23GPL			301	125	13	104	122	10.8
AL	R23AL			337	125	19	107	122	14.4


R23 SPECIFICATIONS Adapters, Accessories




BE




SL



TL



LP



LR



LT

Type	Part. no			A mm	B mm	C mm	D mm	E mm	F mm	G bevel	Weight kg
BE	R23BE40			42	408	120	137	249	130	30°	17.5
BE	R23BE50			52	408	120	137	249	130	30°	17.3
SL	R23SL40			40 (40-50)	404	120	N/A	N/A	127	25°	18.6
TL	R23TL40			42	403	120	244	140	130	25°	18.3
LP	R23LP			28	102						0.3
LR	R23LR			40							-
LT	R23LT			435	69						0.9