




R29 SPECIFICATIONS Teeth




GPE




VE




WE




FE



AE



GPL




AL

Typical machine weight - Excavator 35-45 MT
Maximum breakout force in HD/XHD 233 kN


Typical machine weight - Loader 35-45 MT
Maximum breakout force in HD/XHD 419 kN

Type	Part. no			A mm	B mm	C mm	D mm	E mm	Weight kg
GPE	R29GPE			331	138	15	115	134	12.6
VE	R29VE			365	138	13	14	134	11.4
WE	R29WE			365	138	13	170	134	13.5
FE	R29FE			340	138	18	226	134	17.4
AE	R29AE			361	138	24	136	134	16.2
GPL	R29GPL			331	138	14	115	134	14.5
AL	R29AL			371	138	21	117	134	19.2


R29 SPECIFICATIONS Adapters, Accessories




BE




SL



TL



LP



LR



LT

Type	Part. no			A mm	B mm	C mm	D mm	E mm	F mm	G bevel	Weight kg
BE	R29BE50			52	449	132	150	274	148	30°	23.7
BE	R29BE60			62	449	132	148	274	148	30°	23.2
SL	R29SL50			50 (50-65)	444	132	N/A	N/A	144	25°	21.0
TL	R29TL50			52	443	132	268	156	150	25°	24.6
LP	R29LP			31	112						0.4
LR	R29LR			43							-
LT	R29LT			460	70						1.0